

### CABLE 2x4 + (6x0,14+P)

**2x4 mm<sup>2</sup>**

**Core:** Bare copper. Class 5

**Standard:** IEC 60228

**Insulation:** PVC Tl2

**Color:** Red, Black

**Diameter:** 2,90 mm

**Wiring:** In layers

**6x0,14 mm<sup>2</sup>**

**Core:** Bare copper. Class 5

**Standard:** IEC 60228

**Insulation:** PVC Tl2

**Color:** Black, Blue, Yellow, Green, Brown

**Outer sheat Diameter:** 1,60 mm

**Screen:** Overall Alumium /Polyester Foil

**Drain:** Tinned copper

**Overall Jacket:** 2x4 + 6x0,14:NBR

**Color:** Blue RAL 5015

**Overall Diameter:** 9,7 mm ± 0,2 mm

**Flame retardant:** IEC 60332-1

**Temperature:** -10 °C to +70 °C

### CABLE 2x2,5 + (6x0,14+P)

**2x2,5 mm<sup>2</sup>**

**Core:** Bare copper. Class 5

**Standard:** IEC 60228

**Insulation:** PVC Tl2

**Color:** Red, Black

**Diameter:** 2,40 mm

**Wiring:** In layers

**6x0,14 mm<sup>2</sup>**

**Core:** Bare copper. Class 5

**Standard:** IEC 60228

**Insulation:** PVC Tl2

**Color:** Grey, Grey, Blue, Brown, Yellow, Green

**Outer sheat Diameter:** 1,40 mm

**Screen:** Overall Alumium /Polyester Foil

**Drain:** Tinned copper

**Overall Jacket:** 2x2,5 + 6x0,14:NBR

**Color:** Blue RAL 5015

**Overall Diameter:** 10,50 mm ± 0,2 mm

**Flame retardant:** IEC 60332-1

**Temperature:** -10 °C to +70 °C

