

Kabel voor aansluiting van zwembadtoebehoren.  
Câble pour le raccordement des accessoires de piscine.

### CABLE 2x2,5 + (6x0,14+P)

2x2,5 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Red, Black  
**Diameter:** 2,40 mm  
**Wiring:** In layers

6x0,14 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Grey, Grey, Blue, Brown, Yellow, Green  
**Outer sheat Diameter:** 1,40 mm  
**Screen:** Overall Aluminium /Polyester Foil  
**Drain:** Tinned copper  
**Overall Jacket:** 2x2,5 + 6x0,14:NBR  
**Color:** Blue RAL 5015  
**Overall Diameter:** 9,7 mm ± 0,2 mm  
**Flame retardant:** IEC 60332-1  
**Temperature:** -10 °C to +70 °C

### CABLE 2x4 + (6x0,14+P)

2x4 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Red, Black  
**Diameter:** 2,90 mm  
**Wiring:** In layers

6x0,14 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Black, Blue, Yellow, Green, Brown  
**Outer sheat Diameter:** 1,60 mm  
**Screen:** Overall Aluminium /Polyester Foil  
**Drain:** Tinned copper  
**Overall Jacket:** 2x4 + 6x0,14:NBR  
**Color:** Blue RAL 5015  
**Overall Diameter:** 10,50 mm ± 0,2 mm  
**Flame retardant:** IEC 60332-1  
**Temperature:** -10 °C to +70 °C

### CABLE 2x6 + (6x0,5+P)

2x6 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Red, Black  
**Diameter:** 3,80 mm  
**Wiring:** In layers

6x0,5 mm<sup>2</sup>

**Core:** Bare copper. Class 5  
**Standard:** IEC 60228  
**Insulation:** PVC T12  
**Color:** Grey, Grey, Blue, Brown, Yellow, Green  
**Outer sheat Diameter:** 1,80 mm  
**Screen:** Overall Aluminium /Polyester Foil  
**Drain:** Tinned copper  
**Overall Jacket:** 2x6 + 6x0,5:NBR  
**Color:** Blue RAL 5015  
**Overall Diameter:** 14,80 mm ± 0,2 mm  
**Flame retardant:** IEC 60332-1  
**Temperature:** -10 °C to +70 °C

### Karakteristieken van de kabel / Caractéristiques du câble

